

# Product datasheet

Specifications



## APC 17" Rack LCD Console

AP5717

### Overview

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Presentation | 1U rack-mountable keyboard, mouse, and LCD console with US English keyboard layout. |
|--------------|-------------------------------------------------------------------------------------|

### Main

|                           |                                                                                                                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type | Console                                                                                                                                                                                     |
| Main Input Voltage        | 100 V<br>240 V                                                                                                                                                                              |
| Network frequency         | 50/60 Hz                                                                                                                                                                                    |
| Number of rack unit       | 1U                                                                                                                                                                                          |
| Provided equipment        | C13-C14 power cord<br>Documentation CD<br>Firmware upgrade cable<br>Installation guide<br>NEMA 5-15 power cord<br>PS2 KVM cable<br>Single user rack mount kit<br>USB cable<br>USB KVM cable |

### Complementary

|                           |                            |
|---------------------------|----------------------------|
| Mounting location         | Front<br>Rear              |
| Mounting mode             | Rack-mounted               |
| Minimum mounting depth    | 680 mm                     |
| Maximum mounting depth    | 1049.8 mm                  |
| Display type              | LCD display                |
| Display power consumption | 19 W                       |
| Pixel size                | 0.26                       |
| Trackball type            | PS/2 touchpad<br>USB mouse |
| Colour                    | Black                      |
| Height                    | 44 mm                      |
| Width                     | 482 mm                     |
| Depth                     | 614 mm                     |
| Net weight                | 15.9 kg                    |
| Display colour            | 16 colours                 |
| Display size              | 17 inch                    |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Environmental

|                                       |                                                                                     |
|---------------------------------------|-------------------------------------------------------------------------------------|
| Product certifications                | C-Tick<br>CE<br>Industry Canada<br>KCC<br>NOM<br>UL listed<br>VDE<br>TAA compliance |
| Standards                             | EN 55022 class A<br>EN 55024<br>EN 60950<br>FCC part 15 class A<br>IEC 60950        |
| Ambient air temperature for operation | 0...40 °C                                                                           |

# Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 14.000 cm |
| Package 1 Width              | 68.000 cm |
| Package 1 Length             | 83.800 cm |
| Package 1 Weight             | 17.571 kg |

# Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 56 kg CO2 eq.                                 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 53 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 1 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 1 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                         |
| Packaging without single use plastic   | No                                                                          |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                      |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |
| Halogen-free status                    | Product contains halogen above thresholds                                   |

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 95                                                                                                                                                                                                              |
| End of life manual availability | No need of specific recycling operations                                                                                                                                                                        |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative

---



