Product datasheet

Specifications



APC 19" Rack LCD Console

AP5719

Overview

Presentation	1U rack-mountable keyboard, mouse, and LCD console with US English keyboard layout.

Main

Product or component type	Console
Main Input Voltage	100 V 240 V
Network frequency	50/60 Hz
Number of rack unit	1U
Provided equipment	C13-C14 power cord Documentation CD Firmware upgrade cable Installation guide NEMA 5-15 power cord PS2 KVM cable Rack mounting hardware Single user rack mount kit USB cable USB KVM cable

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Minimum mounting depth	680 mm
Maximum mounting depth	1049.8 mm
Display type	LCD display
Display power consumption	19 W
Pixel size	0.26
Trackball type	PS/2 touchpad USB mouse
Colour	Black
Height	44 mm
Width	482 mm
Depth	665 mm
Net weight	17.4 kg
Display size	19 inch

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	C-Tick CE Industry Canada KCC NOM UL listed VCCI class A VDE TAA compliance
Standards	EN 55022 class A EN 55024 EN 60950 FCC part 15 class A IEC 60950
Ambient air temperature for operation	0…40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	82.6 cm
Package 1 Length	67.3 cm
Package 1 Weight	20.99 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**61 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**58 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
Halogen-free status	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative




APC

