

Product datasheet

Specifications



Rack PDU, Basic, 1U, 22kW, 400V, (6) C19



AP7526

Main

Product or component type	PDU
Main Input Voltage	400 V 3 phases
Input current limits	32 A
Network frequency	47...63 Hz
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 3P + N + PE
Number of power socket outlets	6 IEC 60320 C19
Load capacity	22000 VA
permissible voltage	200...250 V
Max current draw	32 A
Max line current	32 A
PDU type	Basic
Protection type	Circuit breaker
Number of rack unit	1U
Number of cables	1
Cable length	2.4 m
Provided equipment	Installation guide

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44 mm
Width	437 mm
Depth	254 mm
Net weight	4.84 kg

Environmental

Product certifications	CE GOST VDE
Relative humidity	5...95 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	5...95 %
Ambient air temperature for storage	-25...65 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	55.9 cm
Package 1 Length	50.2 cm
Package 1 Weight	6.965 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	9 565 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	9 540 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

