

Product datasheet

Specifications



APC NetShelter Basic Rack PDU, Zero U, 32A, 230V, 20 C13 and 4 C19 outlet, IEC309 inlet

AP7553

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	32 A
Network frequency	47...63 Hz
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of power socket outlets	20 IEC 60320 C13 4 IEC 60320 C19
Load capacity	7400 VA
Max current draw	32 A
PDU type	Basic
Number of rack unit	0U
Number of cables	1
Cable length	3 m
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Height	1619 mm
Width	56 mm
Depth	44 mm
Net weight	5.57 kg

Environmental

Product certifications	CE VDE
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Ambient air temperature for storage	-25...65 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage altitude	0...15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	15.000 cm
Package 1 Length	212.000 cm
Package 1 Weight	8.943 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	120.000 cm
Package 2 Length	222.000 cm
Package 2 Weight	101.700 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 476 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 452 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

