

Product datasheet

Specifications



APC NetShelter Metered Rack PDU, 1U, 16A, 208/230V, 8 C13 outlet



AP7821B

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	20 A
Network frequency	50/60 Hz
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of power socket outlets	8 IEC 60320 C13
Load capacity	3300 VA
[In] rated current	16 A
Max current draw	20 A
PDU type	Metered
Protection type	Without circuit breaker
Number of rack unit	1U
Cable length	2.4 m
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44 mm
Width	444 mm
Depth	102 mm
Net weight	1.74 kg

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	cUL listed C-Tick CE CSA GOST UL listed VCCI VDE
Standards	FCC part 15 class A ICES-003 UL 60950
Relative humidity	5...95 %
Storage Relative Humidity	5...95 %
Ambient air temperature for storage	-25...65 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	33.7 cm
Package 1 Length	47 cm
Package 1 Weight	2.92 kg

Contractual warranty

Warranty (in months)	24
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	1 983 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	53 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 927 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	53
End of life manual availability	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



