

# Product datasheet

Specifications



## Power Cord Kit (6 ea), Locking, C19 to C20 (90 Degree), 1.2m

AP8714R

### Overview

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentation | Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads. |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Main

|                           |                                                         |
|---------------------------|---------------------------------------------------------|
| Product or component type | Power cord                                              |
| Input current limits      | 16 A                                                    |
| Input Connection Type     | IEC 60320 C20                                           |
| Max current draw          | 16 A                                                    |
| Max line current          | 16 A                                                    |
| Number of cables          | 6                                                       |
| Cable length              | 1.21 m                                                  |
| Power cable length        | 1.2 m                                                   |
| Provided equipment        | 3 left-angle jumper cords<br>3 right-angle jumper cords |

### Complementary

|                     |                    |
|---------------------|--------------------|
| Mounting preference | No preference      |
| Mounting mode       | Not rack-mountable |
| Height              | 300 mm             |
| Width               | 65 mm              |
| Depth               | 70 mm              |
| Net weight          | 1.64 kg            |

### Environmental

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Product certifications              | CCC<br>CSA<br>PSE<br>UL listed<br>VDE |
| Relative humidity                   | 20...80 %                             |
| Storage Relative Humidity           | 20...80 %                             |
| Ambient air temperature for storage | -25...75 °C                           |
| Storage altitude                    | 0...15240 m                           |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |              |
|---------------------------------------|--------------|
| Operating altitude                    | 0...10000 ft |
| Ambient air temperature for operation | 0...75 °C    |

## Packing Units

|                              |                |
|------------------------------|----------------|
| Unit Type of Package 1       | PCE            |
| Number of Units in Package 1 | 1              |
| Package 1 Height             | 30 cm          |
| Package 1 Width              | 6.5 cm         |
| Package 1 Length             | 7 cm           |
| Package 1 Weight             | 1.64 kg        |
| Unit Type of Package 2       | PAL            |
| Number of Units in Package 2 | 9              |
| Package 2 Height             | 143.99 cm      |
| Package 2 Width              | 100 cm         |
| Package 2 Length             | 120 cm         |
| Package 2 Weight             | 14.733 kg      |
| Unit Type of Package 3       | CAR            |
| Number of Units in Package 3 | 9              |
| Package 3 Height             | 25 cm          |
| Package 3 Width              | 33.5 cm        |
| Package 3 Length             | 56.5 cm        |
| Package 3 Weight             | 14.733 kg      |
| SCC14                        | 10731304279690 |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 143 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 8 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0.7 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 132 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 3 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                                |                                                                             |
|------------------------------------------------|-----------------------------------------------------------------------------|
| Average percentage of recycled plastic content | 15 %                                                                        |
| Packaging made with recycled cardboard         | Yes                                                                         |
| Packaging without single use plastic           | Yes                                                                         |
| SCIP Number                                    | 1cdb2fed-a06f-4574-913d-8df8e70936b2                                        |
| EU RoHS Directive                              | <a href="#">Compliant</a>                                                   |
| REACH Regulation                               | <a href="#">Free of Substances of Very High Concern above the threshold</a> |
| Halogen-free status                            | Product contains halogen above thresholds                                   |

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 30                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |