

Product datasheet

Specifications



Power Cord, C19 to CEE/7 Schuko, 2.5m



AP9875

Main

Product or component type	Power cord
Input current limits	16 A
Input Connection Type	Schuko CEE 7 / EU1-16P
Max current draw	16 A
Max line current	16 A
Number of rack unit	0U
Number of cables	1
Cable length	2.4 m

Complementary

Mounting preference	No preference
Mounting mode	Not rack-mountable
Net weight	0.22 kg

Environmental

Product certifications	VDE
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Ambient air temperature for storage	-25...65 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	10.2 cm
Package 1 Length	20.3 cm
Package 1 Weight	0.299 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	25.5 cm
Package 2 Width	33.2 cm
Package 2 Length	53.6 cm
Package 2 Weight	4.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	10
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	4.5 kg

Contractual warranty

Warranty (in months)	24
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	30 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	29 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again

 Repack and remanufacture	
Recyclability potential, in %	30
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins