

Product datasheet

Specifications



APC NetShelter SX, Server Rack Enclosure, Colocation, 42U, Black, 1991H x 600W x 1070D mm

AR3200

Overview

Presentation	Two compartment enclosure for colocation facilities with customers requiring a minimal amount of rack space. This multi-tenant, security enhanced enclosure is provided with a compact width to optimize data center space.
--------------	---

Main

Product or component type	Rack enclosure
Number of rack unit	42U
Rack width	19"
Permanent permissible load	1020.6 kg dynamic 1701.0 kg static
Provided equipment	3-digit combination style handles Adjustable vertical mounting rails Baying hardware Documentation CD Door key Installation guide Leveling feet Pre-installed casters Rack mounting hardware Roof

Complementary

Mounting mode	Not rack-mountable
Maximum mounting depth	944.9 mm
Colour	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	1991 mm
Width	600 mm
Depth	1070 mm
Net weight	140.7 kg

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	211.7 cm
Package 1 Width	74.6 cm
Package 1 Length	115.6 cm
Package 1 Weight	168.35 kg

Contractual warranty

Warranty (in months)	60
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	591 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	564 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	13 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative







