

Product datasheet

Specifications



APC Back-UPS Pro, 1300VA/
780W, Tower, 230V, 8x IEC C13
outlets, AVR, LCD, User
Replaceable Battery

BR1300MI

Main

Main input voltage	230 V AC 1 phase
Input connection	IEC 60320 C14
Maximum input current	10 A
Switching current capacity	10 A
Efficiency at full load	176...294 V
Input frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	780 W
Rated power in VA	1300 VA
Output connection	6 IEC 60320 C13 2 IEC 60320 C13 surge
Type of USB power supply	None
Maximum configurable power in VA	1300 VA
Maximum configurable power in W	780 W
UPS topology	Line interactive
Output frequency	50/60 Hz +/- 1 Hz sync to mains
Replacement battery	APCRBC165

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery capacity	6.0 Ah
Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	USB port
Surge energy rating	509 J
Noise filtering	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Color	Black

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	100 mm
Width	250 mm
Depth	382 mm
Product weight	10.2 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Back-UPS Pro
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	45 dBA
Heat dissipation	21.5 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	16 h
RBC quantity	1
Battery life	3...5 year(s)

Battery charging power	11 W rated
------------------------	------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	22.5 cm
Package 1 Length	48.5 cm
Package 1 Weight	11.85 kg
SCC14	10731304346903

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	422 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	114 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	306 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	019b51cf-d7f1-4f06-ac85-1378fc94c7aa
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

Use Again



Repack and remanufacture

Recyclability potential, in %	62
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



