

Product datasheet

Specifications



APC Easy UPS 900VA, Tower, 230V, 4 NEMA UNIVERSAL Outlets, AVR

BVG900I-MSN

Main

Main input voltage	220...240 V AC 1 phase
Input connection	NEMA 5-15P 4.1 A
Input protection	Circuit breaker
Input frequency	50/60 Hz +/- 5 Hz indoor use only
Output voltage	230 V AC 1 phase
Rated power in W	480 W
Rated power in VA	900 VA
Output connection	4 universal
Output connection	Universal
Type of USB power supply	None
Maximum configurable power in W	375 W
Output voltage tolerance	+/- 10 %
Transfer time	6 ms typical : 10 ms maximum
UPS topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Full load runtime	00:00:01 480 W
Half load runtime	00:03:48 240 W

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Emergency power off	No
Alarm	Alarm when on battery : distinctive low battery alarm : high temperature : overload continuous tone alarm
Surge energy rating	156 J
Color	Black
Height	142 mm
Width	101 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	300 mm
Product weight	4.9 kg
USB compatible	No
Mounting mode	Desktop installation compact
Max runtime	0.01 min
Range of product	Easy UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...3000 m
IP protection	IP20 indoor use only
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	< 40 dBA
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	VRLA
Extendable runtime	0
RBC quantity	0
Battery design life	3...5 year(s)
Battery life	3...5 year(s)
Battery charging power	14 W indoor use only

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.2 cm
Package 1 Width	10.1 cm
Package 1 Length	30 cm
Package 1 Weight	4.9 kg
SCC14	10731304769603

Contractual warranty

Warranty (in months)	24 UPS
----------------------	--------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	493 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	78 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	398 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	12 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	70 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	33
End of life manual availability	End of Life Information
Removable battery	No
Take-back	No

Image of product / Alternate images

Alternative



