

Product datasheet

Specifications



APC Smart-UPS X-Series External Battery Pack Rack/Tower 120V, 1200VAh, rackmount, 4U

SMX120BP

Main

Product or component type	External battery pack
Number of rack unit	4U
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets
Range of product	Smart-UPS Battery Systems
Replacement battery	APCRBC143

Batteries & Runtime

Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	120 V

Physical

Colour	Black
Height	432 mm
Width	178 mm
Depth	483 mm
Net weight	60.91 kg
Mounting mode	Rack-mounted

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	58.6 cm
Package 1 Length	63.3 cm
Package 1 Weight	65.45 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	300 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	242 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	16 kg CO2 eq.
Carbon footprint of the installation phase [A5]	18 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	228 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	23 kg CO2 eq.

Use Better



Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative





