

Product datasheet

Specifications



APC Easy UPS On-Line SRV
Battery Pack (6/10kVA) for
Extended Runtime Model 240V,
2160VAh, rackmount with kit, 3U

SRV240RLBP-9A

Main

Product or component type	External battery pack
Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	User manual Battery cable Rack mounting brackets
Range of product	Easy UPS On-Line

Batteries & Runtime

Number of battery blocks per string	20
Device mounting	Rack mount
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	240 V

Physical

Colour	Black
Height	133 mm
Width	438 mm
Depth	606 mm
Net weight	63 kg
Mounting mode	Rack-mounted with kit
USB compatible	No

Conformance

Product certifications	CE UKCA EAC EN/IEC 62040-1
------------------------	-------------------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	87 cm
Package 1 Length	58 cm
Package 1 Weight	70 kg

Contractual warranty

Warranty (in months)	24
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	321 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	259 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	17 kg CO2 eq.
Carbon footprint of the installation phase [A5]	20 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	244 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	25 kg CO2 eq.

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	48
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

