

Product datasheet

Specifications



APC Easy UPS On-Line, 2000VA,
Lithium-ion, Rack/Tower 4U, 230V,
6 IEC C13 outlets, Intelligent Card
Slot, Extended runtime, W/ rail kit

SRVL2KRILRK

Overview

Presentation	Double-conversion On-line UPS with Lithium-Ion battery to scalable runtime. Ideal UPS for essential power protection needs even in the most unstable power conditions.
--------------	--

Main

Main input voltage	230 V AC 1 phase
Other input voltage	230 V
Input connection	IEC 60320 C20
Efficiency at full load	160...300 V full load 110...300 V 60 % load
Input frequency	40...70 Hz auto-sensing
Output voltage	230 V AC 1 phase
Other output voltage	220 V 240 V
Rated power in W	1800 W
Rated power in VA	2000 VA
Output connection	6 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Maximum configurable power in VA	2000 VA
Maximum configurable power in W	1800 W
UPS topology	On-Line
Waveform type	Sine wave
Efficiency	90 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery type	Li-Ion (Lithium-Ion) external included
Control panel	Multifunction LCD status and control console
Emergency power off	Yes

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	945 J
Number of rack unit	4U
Color	Black with silver front bezel
Height	172 mm
Width	438 mm
Depth	616 mm
Product weight	37.1 kg
USB compatible	Yes
Mounting position	Horizontal and vertical
Mounting mode	Rack-mounted with included kit
Provided equipment	Basic UPS signalling RS-232 cable USB cable RJ45 cable RJ11 cable C13-C14 power cord IEC-C20 - Shuko input power cord Rack mounting brackets Stabilization feet User manual Safety guide Battery cable
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CB CE RCM EAC TISI UKCA KC UN 38.3 IEC 62619
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15000 m
IP protection	IP20
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	50 dBA
Heat dissipation	683 Btu/h
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Li-Ion (Lithium-Ion)
Battery voltage	48 V
Extendable runtime	1
Included battery module	0
Empty battery slot	0
Typical recharge time	4.8 h
Battery life	8...10 year(s)
Battery charging power	480 W
Battery power in VAh	2569 VAh runtime

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	48 cm
Package 1 Width	8 cm
Package 1 Length	60 cm
Package 1 Weight	50.15 kg

Contractual warranty

Warranty (in months)	60 Battery 36 UPS
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 422 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 068 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	13 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 332 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	58
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative





